

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 7,018,847 B2  
APPLICATION NO. : 09/848417  
DATED : March 28, 2006  
INVENTOR(S) : Ib Mednel-Hartvig et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claim 1, column 9, line 48, after "matrix", insert --, having an upstream end and a downstream end,--.

Claim 1, column 9, line 53, after "analyte," insert --the flow matrix further comprising a diffusively movable detection reagent,--.

Claim 1, column 9, line 54, change "wicking member" to --separate wicking member located--.

Claim 1, column 10, line 7, after "in contact with", insert --a top surface of--.

Claim 1, column 10, line 8, after "wicking member", delete "at a variable position between the upstream and downstream ends of the wicking member, thereby permitting variation of the time elapsing from the application of liquid to the liquid application zone until the indicator substance or substance combination changes colour".

Claim 1, column 10, lines 15-16, change "included on an inner side of" to --located within--.

Claim 6, column 10, line 29, delete "or the inner side of the housing".

Claim 7, column 10, line 33, delete "or on the inner side of the housing".

Column 10, line 55, insert --13. The device according to claim 1, wherein the indicator is included on an inner side of the housing.--.

Signed and Sealed this

Eighteenth Day of March, 2008



JON W. DUDAS  
*Director of the United States Patent and Trademark Office*